

CAT V-Flange End Mill Holders



| Stock No. | CT*d-L1 | L(mm) | D(mm) | D1(mm) | L2(mm) | L3(mm) |
|-----------|--------------------|-------|-------|--------|--------|--------|
| 1175-4001 | CT40*3/16"-2-1/2" | 131.8 | 19.05 | 44.45 | 14.3 | |
| 1175-4002 | CT40*1/4"-2-1/2" | 131.8 | 20.26 | 44.45 | 19.8 | |
| 1175-4003 | CT40*5/16"-2-1/2" | 131.8 | 22.52 | 44.45 | 19.8 | |
| 1175-4004 | CT40*3/8"-2-1/2" | 131.8 | 32 | 44.45 | 19.8 | |
| 1175-4005 | CT40*7/16"-2-1/2" | 131.8 | 31.75 | 44.45 | 22.2 | |
| 1175-4006 | CT40*1/2"-2-5/8" | 134.9 | 44.45 | 44.45 | 22.2 | |
| 1175-4007 | CT40*5/8"-3-3/4" | 163.5 | 44.45 | 44.45 | 23.8 | |
| 1175-4008 | CT40*3/4"-3-3/4" | 163.5 | 44.45 | 44.45 | 25.4 | |
| 1175-4009 | CT40*7/8"-4" | 169.9 | 52 | 44.45 | 27 | 22.2 |
| 1175-4010 | CT40*1"-4" | 169.9 | 63 | 44.45 | 28.6 | 25.4 |
| 1175-4011 | CT40*1-1/4"-4-1/8" | 173 | 69.85 | 44.45 | 28.6 | 25.4 |

Features: Suitable for CNC RPM≥12000 RPM≥20000 balance toolholders are available

HITECH (Qingdao)
ENTERPRISES INC