

1024-0130...0149,1024(F2) SUPER SPACER



Type 1024(F2) super spacer is designed for using and indexing in both horizontal and vertical position. it is the most optimum in use for milling machines, grinding machines, drilling machines planer etc. The divisions in 2,3,4,6,8,12,24 are permitted by notched plate,any desired angular indexing can be performed too by using a graduated ring on the spindle and a verner.

Main specifications

Specifications	Items	1024-0149(F2)	1024-0130(F2-6)
Center height mm		149.25	130
Center diameter of the spindle mm		φ 119.774-	φ 80
Divisions		2, 3, 4, 6, 8, 12, 24	2, 3, 4, 6, 8, 12, 24
Height between external centring diameter of the spindle to the base (in vertical position)mm		96	89.5
Locating diameter of the spindle mm		φ 212	φ 170
Width of the locating key mm		16	16
Matched chuck		K31210A	K31167
24 divisions individual error		25"	25"
Net weight Kg		52	33
Gross weight Kg		60	39
Case dimensions mm		405X370X345	372X340X304

1024-0130...0149,1024(F2) : Inatallation sketch and dimensions

	A	B	C	D	E	F	G	H	I	J	K
1024-0149 (F2)	310	255	φ 210	255.25	18	214	171.5	149.25	80	150	16
1024-0130 (F2-6)	260	220	φ 167	220	18	197.5	155.5	130	70	130	16

**HITECH** (Qingdao)  
**ENTERPRISES INC**