

Twin Hardness Tester

HRRS-150



Accessories:

- Diamond Conical Indentor
- 2- HRC Test Blocks
- 1- HR15N Test Block
- 1- HR45T Test Block
- Flat Anvil 2.5" (63mm)
- Accessory Case
- 1/16" Ball Indentor
- 1- HRB Test Block
- 1- HR30N Test Block
- Test Table 5.87" (150mm)
- Std. Vee Anvil
- Dust Cover

HRRS-150

Test Rockwell and Superficial Rockwell Hardness in 1 Unit!

The HRRS-150, tests both Rockwell hardness and Superficial Rockwell hardness in one unit . The Twin Rockwell/Superficial Rockwell hardness tester is ruggedly engineered to obtain highly sensitive and accurate readings. Conforming to ASTM E-18 Rockwell hardness standards, this hardness tester will offer unmatched repeatability in all Rockwell hardness scales. A perfect performer suited for any environment including heat treatment facilities, tool rooms, workshops, laboratories and inspection labs.

Perfect for laboratories, workshops, tool rooms, inspection labs, etc.

Specifications:

Minor Load	3 Kgf, 10 Kgf
Major Load	15Kgf 30 Kgf 45 Kgf 60 Kgf 100 Kgf 150 Kg
Test Force Application	Dead Weight
Test Force Control	Manual
Results Display	Dual Scale Dial
Vertical Capacity	6.0 in.
Throat Depth	5.5 in.
Height	26.0 in.
Width	18.2 in.
Depth	9.4 in.
Shipping Weight	250 lbs

Hardness Scales: HRA B,C,D,E,F,G,H,K , L, M (superficial) HR15N, HR15T, HR30N, HR30T, HR45N, HR45T

Features: Model No. HRRS-150

- · Direct analog dial reading
- · Advanced design, easy to operate
- Engineered to obtain highly sensitive and accurate readings

ADD: T2-17A, 35 Donghai West Road, Pacific Plaza, Qingdao, P.R.China 266071 HTTP: //www.hitechcn. FAX: +86-532-85022177 TEL: +86-532-85022176 EMAIL: contact@hitechcn.com

